

Dkt. No: BU5EJ-P03  
Appln. No.: 10/572,757  
Reply to Office action of 21DEC2004

BEST AVAILABLE COPY

Amendments to the Claims

The listing of claims below will replace prior versions, and listing, of claims in the application:

Listing of Claims

- 5 1. (currently amended) A dust-capturing device for a power saw having a foot plate, a blade guard and a guide on the blade guard with a channel disposed on the guide, said dust-capturing device comprising:
- 10 (a) a hollow capture member having a first end with an opening thereat and a second end with an opening thereat;
- (b) a support member securable to said capture member;
- (c) a mounting member attached to said support member and adapted to secure said capture member within the channel of the power; and
- 15 (d) an adjustment means for adjusting said device to accommodate varying depths of cut made by a user wherein said adjustment means comprises a pivot connection between said mounting member and the channel on the guide.
- 20 2. (original) The device as defined in Claim 1 further comprising a registration means for registering said support member to said first end of said capture member.

AMDT: Page 3 of 6

Dkt. No: BUSEJ-P03  
Appin. No.: 10/672,757  
Reply to Office action of 21DEC2004

REPLY

3. (original) The device as defined in Claim 2, wherein said registration means comprises a projection and cooperating groove on said support member and said first end of said capture member.

5 4. (original) The device as defined in Claim 3 wherein said projection and cooperating groove bear any geometric shape selected from the group consisting of squared, rectilinear, triangular, and rounded.

10 5. (original) The device as defined in Claim 3 wherein said projection is a longitudinal projection of said first end of said capture member and said cooperating groove is disposed on an inner surface of said support member.

15 6. (original) The device as defined in Claim 3 wherein said projection is disposed on an inner surface of said support member and said cooperating groove is a longitudinal groove on said first end of said capture member.

7. (deleted)

8. (currently amended) The device as defined in Claim 1 [[7]] wherein said adjustment means further comprises a pivot connection between said support member and said mounting member.

AMDT: Page 4 of 6

Dkt. No: BUSEJ-P03  
Appln. No.: 10/672,757  
Reply to Office action of 21DEC2004

9. (deleted)

10. (currently amended) The device as defined in Claim 1 [[9]]  
wherein said adjustment means further comprises a translating  
connection at said pivot connection between said mounting member  
5 and the channel on the guide.

11. (original) The device as defined in Claim 1 wherein the  
opening at said first end is disposed at an angle between 0° and  
approximately 80°.

12. (original) The device as defined in Claim 1 wherein the  
10 opening at said first end is disposed at an angle between  
approximately 30° and approximately 60°.

AMDT: Page 5 of 6

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☒ BLACK BORDERS

☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES

☐ FADED TEXT OR DRAWING

☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING

☐ SKEWED/SLANTED IMAGES

☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS

☐ GRAY SCALE DOCUMENTS

☒ LINES OR MARKS ON ORIGINAL DOCUMENT

☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**